

REPAIR SHEET - Rear lamp replacement (EN)

REASON:

OPERATOR	WORKSHOP	DATE
REGISTRATION	TIME 0h 5min	COST

REQUIRED TOOLS			SAFETY	
☐ 10mm open-end wrench	☐	☐	☐ Safety shoes	
☐	☐	☐	☐ Safety gloves	
☐	☐	☐	☐	
☐	☐	☐	☐	
☐	☐	☐	☐	

	TOOLS	PROCESS	ASSEMBLY DRAWING	ESTIMATED TIME
1		Rear lamp disconnection: 1- Manually remove the cable cover cap. 2- Identify and remember the position of the electrical connectors before removal, as they may vary depending on the vehicle. 3- Disconnect the electrical connectors.		2
		REMARKS		REAL TIME
2	10mm open-end wrench	Rear lamp removal: 1- Using a 10 mm open-end wrench, loosen and remove the two mounting nuts of the rear lamp. 2- Remove the rear lamp and carefully pull out the wires, one by one.		1
		REMARKS		REAL TIME
3	10mm open-end wrench	Rear lamp installation: 1- Insert the wires of the new rear lamp and position the rear lamp in place. 2- Using a 10 mm open-end wrench, tighten the two rear lamp mounting nuts.		1
		REMARKS		REAL TIME

TOOLS		PROCESS	ASSEMBLY DRAWING	ESTIMATED TIME
4	Rear lamp connection: 1- Connect the rear lamp in the same way as originally and place the wiring inside the cable cover. 2- By hand, install the cable cover cap.			1
	REMARKS		REAL TIME	