

REPAIR SHEET - SEAT REPLACEMENT

REASON:

OPERATOR

WORKSHOP

DATE

REGISTRATION

TIME

0h 10min

COST

REQUIRED TOOLS

SAFETY

☐	13mm Open-ended wrench	☐		☐		☐	
☐	13mm Socket	☐		☐		☐	
☐	Medium ratchet wrench	☐		☐		☐	
☐		☐		☐		☐	
☐		☐		☐		☐	

TOOLS

PROCESS

ASSEMBLY DRAWING

ESTIMATED TIME

Seat Removal.

1- Using a medium socket and a 13mm wrench, remove the bolt securing the seat belt, holding the nut with a 13mm wrench.

2- Pull the seat back and, using a medium socket and a 13mm wrench, remove the two front bolts.

3- Pull the seat forward and remove the two rear bolts, then remove the seat.



5

REMARKS

REAL TIME

1

TOOLS		PROCESS	ASSEMBLY DRAWING	ESTIMATED TIME
2	13mm Open end wrench, 13mm wrench socket, Medium ratchet wrench.	Seat Installation 1- Position the seat and loosely tighten the two rear screws. 2- Slide the seat back, tighten the two front seat screws, and then tighten the front and rear screws. 3- Pass the bolt through the seat belt mounting plate and the seat. Tighten the nut using a 13mm open-end wrench, a medium-sized socket, and a 13mm socket.		5
		REMARKS		REAL TIME