

REPAIR SHEET - SIDE SKIRTS REPLACEMENT

REASON:

OPERATOR	WORKSHOP	DATE
REGISTRATION	TIME 0h 12min	COST

TOOLS				SAFETY	
☐	Allen key	☐		☐	Safety gloves
☐		☐		☐	Safety shoes
☐		☐		☐	
☐		☐		☐	
☐		☐		☐	

TOOLS	PROCESS	ASSEMBLY DRAWING	ESTIMATED TIME
1	Box removal : 1- Refer to the box removal sheet.		5
REMARKS			REAL TIME
2	Allen key Removal of the side skirts: 1- Using an Allen key, loosen and remove the four mounting screws securing the side skirts (two on the left-hand side and two on the right-hand side). 2- Remove the side skirts by pulling them toward the rear of the vehicle and then lifting them to completely release them.	  	1
REMARKS			REAL TIME
3	Allen key Installation of the side skirts: 1- Position the new side skirts in their mounting locations. 2- Using an Allen key, install and tighten the four mounting screws securing the side skirts.	 	1
REMARKS			REAL TIME

4	TOOLS	PROCESS	ASSEMBLY DRAWING	ESTIMATED TIME
		Box installation : 1- Refer to the box installation sheet.		5
	REMARKS			REAL TIME